FLEXMAR®

FLEXMAR® Variegate™

Polyaspartic Stain Sealer

For a ***Natural, Marble-Like, Stone-Like*** Appearance

We've added two new colors!

THE ONE • THE ONLY

The Original

Transform Your Floor From This

To This

With the Stroke of a Brush

Give your surface a refined, sophisticated look with the rugged durability of a FLEXMAR polyaspartic coating

- Combines a semi-transparent stain and wear surface sealer in one product
- Eliminates acid staining
- Achieves a natural, marble-like, stone-like appearance with one or more color combinations
- Extends life cycle to four times that of alternative stains and sealers
- 1- to 2-hour walk-on and return to service
- Offers excellent adhesion to prepared concrete, overlayments, and wood decking
- Provides excellent outdoor resistance to UV rays, color change, and fading
- Apply year-round indoors or outdoors—even in cold weather!
- Manufactured with select polyaspartic resins from Bayer MaterialScience

FLEXMAR® Variegate™ polyaspartic stain sealers feature a variety of colors for a natural look without fading or yellowing with age or exposure to sunlight

Amber

Saddle Brown

Mahogany

Olive

Sumatra

Copper

Sapphire Blue

Ebony

Check with your local distributor for more colors.

FLEXMAR sets the performance standard for polyaspartic coatings versus other coatings

Superior Abrasion Wear Resistance

2-Pack Epoxy vs. Aliphatic Polyurethane vs. FLEXMAR Fast-Cure Polyaspartic

ASTM D-968 – Falling Sand Abrasion - Liters of Falling Sand to Erode 1 Dry Mil of Coating

FLEXMAR fast-cure polyaspartic coatings are nearly 4 times more abrasion-resistant than 2-pack epoxy coatings and at least 25% better than aliphatic polyurethane coatings.

Remarkable Walk-On Time at ≤55°F

2-Pack Epoxy vs. Aliphatic Polyurethane vs. FLEXMAR Fast-Cure Polyaspartic

Applied at 55°F or lower, FLEXMAR fast-cure polyaspartic coatings can be walked on in just 2 hours–34 hours sooner than aliphatic polyurethane coatings and days sooner than 2-pack epoxy coatings. In most cases, 2-pack epoxy coatings are not recommended for application below 55°F.

If it isn't FLEXMAR, it's just another coating.

Your FLEXMAR Certified Installer:

FLEXMAR®
COATINGS, LLC

Toll-Free: 877-339-1442
www.flexmarpolyaspartics.com

Information in this brochure is the property of FLEXMAR Coatings, LLC and may not be used without the express consent of FLEXMAR Coatings.

Copyright © 2010, 2011. FLEXMAR Coatings, LLC.